LED Technologies
Creative LED & Effect Technology for the Trade Professional

Studio Flex

StudioFlex CT Adjustable LED Strip 2800-6500K CRI>80 24V 96W IP20



Product Code:	100.520
Product Type:	StudioFlex LED Strip
Guarantee Period:	5 Years


Features & Benefits:

- Professional grade lighting solution
- Dynamic 2800-6500CCT Adjustable
- 60 x 5050 Bi-Colour LED's Per Metre
- 100mm Cut Intervals
- Built with high quality materials
- 5 Year warranty
- 5 Metre Roll
- CRI >80

150g *appx* **2oz** *PCB Weight* 24V

Colour Temperature:	2800-6500K
Power	96W
Current:	830mA/M
Input Voltage:	24V DC
Cut Intervals:	100mm
LED Quantity:	60 LEDs per Metre
LED Spacing:	16.7mm
LED Type:	SMD5050 2 colors in ONE LED
Size:	10x2x5000mm Roll
CRI Rating:	>80
Dimmable:	Yes
Lumens per LED:	25lm per LED
Lumens per Metre:	1450m /m
Light intensity per LED:	7000-7500mcd
Power Consumption per Metre:	19.2W
IP Rating:	IP20
Average LED Lifetime:	50,000 Hours
Reel Length:	5m
Peelable Back:	300LSE 3M adhesive tape
CE & RoHS:	Yes
Continuous Run:	5 metres
Base Type:	30cm tails on each end

Dimensions (Unit: mm)



Notes:

- The LED Strip cutting points are situated 100mm apart from each other. The cutting marks are located on the three copper tabs every 100mm . The LED Strip must **NOT** be cut anywhere else.
- This StudioFlex RGB LED Strip features 60 LEDs per metre, perfect for professional applications

UK CA | CE | RoHS Compliant

We reserve the right to change specifications without notice. E&OE

If you require Technical support or for general enquiries, please do not hesitate to contact one of our LED Technical experts on the contact information provided.


Telephone: 01260 540014
Opening times: Mon-Thur: 8:30am - 5:00pm
Fri: 8:30am - 4:30pm
www.ledtechnologies.co.uk

LED Technologies
Creative LED & Effect Technology for the Trade Professional

Studio Flex

StudioFlex CT Adjustable LED Strip 2800-6500K CRI>80 24V 96W IP20

100.520 Connection Diagram





Sunricher RGBW RF Controller

SR2819SP

Example of RF Control Method

Notes:

- The StudioFlex Strip is powered by 96W, so we recommend a **125W LED Driver** to safely power **5 Metres** of the strip.
- Ensure that the LED Strip wires are connected to the correct terminals on the suitable LED Receiver chosen. Please see the diagram above for the correct terminals to attach each wire to.
- **Our range of LED Strip is not limited to RF Control Methods. Many other control options are available for the LED Strip including DMX, DALI ZiGBEE & more.*

+10% Tolerance on all Specifications. Colours can be variable.
We reserve the right to change specifications without notice. E&OE

If you require Technical support or for general enquiries, please do not hesitate to contact one of our LED Technical experts on the contact information provided.

Telephone: 01260 540014
Opening times: Mon-Thur: 8:30am - 5:00pm
Fri: 8:30am - 4:30pm
www.ledtechnologies.co.uk