LED Technologies
Creative LED & Effect Technology for the Trade Professional

Studio Flex

StudioFlex Warm White LED Strip 2600-2800K 24V 96W IP20



Product Code:	100.605
Product Type:	StudioFlex
Guarantee Period:	5 Years

Features & Benefits:


- Warm White 2600-2800K
- 240 x 3528 LED's Per Metre
- 25mm Cut Intervals
- Rich warm white light
- Minimum pixilation
- 5 Year warranty
- 5 Metre Roll
- Professional grade lighting solution

150g /roll *appx*

2oz *PCB Weight*

Colour:	2600-2800K
Power	96W
Current:	800mA/M
Input Voltage:	24V DC
Cut Intervals:	25mm
LED Quantity:	240 LEDs per Metre
LED Spacing:	4.2mm
LED Type:	SMD3528
Size:	10x2.2x5000mm Roll
CRI Rating:	>80
Dimmable:	Yes
Lumens per LED:	6-7lm per LED
Lumens per Metre:	1800lm /m
Light intensity per LED:	2100mcd
Power Consumption per Metre:	19.2W
IP Rating:	IP20
Average LED Lifetime:	50,000 Hours
Reel Length:	5m
Peelable Back:	300LSE 3M adhesive tape
CE & RoHS:	Yes
Continuous Run:	5 metres
Base Type:	30cm tails and 30cm cable+DC connector

Dimensions (Unit: mm)



Notes:

- The LED Strip cutting points are situated 25mm apart from each other. The cutting marks are located on the two copper tabs every 25mm. The LED Strip must **NOT** be cut anywhere else.
- This StudioFlex LED Strip features 240 LEDs per metre, perfect for professional applications

UK CA | CE | RoHS Compliant

We reserve the right to change specifications without notice. E&OE

If you require Technical support or for general enquiries, please do not hesitate to contact one of our LED Technical experts on the contact information provided.

Telephone: 01260 540014
Opening times: Mon-Thur: 8:30am - 5:00pm
Fri: 8:30am - 4:30pm
www.ledtechnologies.co.uk


LED Technologies
Creative LED & Effect Technology for the Trade Professional


Studio Flex

StudioFlex Warm White LED Strip 2600-2800K 24V 96W IP20

100.605 Connection Diagram

RF Dimming Control Example





Sunricher Single Colour RF Controller

SR2819SDIM

Example of RF Control Method

Notes:

- The StudioFlex Strip is powered by 100W, so we recommend a **150W LED Driver** to safely power **5 Metres** of the strip.
- Ensure that the LED Strip wires are connected to the correct terminals on the suitable LED Receiver chosen. Please see the diagram above for the correct terminals to attach each wire to.
- **Our range of LED Strip is not limited to RF Control Methods. Many other control options are available for the LED Strip including DMX, DALI ZiGBEE & more.*

+10% Tolerance on all Specifications. Colours can be variable.
We reserve the right to change specifications without notice. E&OE

If you require Technical support or for general enquiries, please do not hesitate to contact one of our LED Technical experts on the contact information provided.

Telephone: 01260 540014
Opening times: Mon-Thur: 8:30am - 5:00pm
Fri: 8:30am - 4:30pm
www.ledtechnologies.co.uk