ELG-300

300W Constant Voltage + Constant Current LED Driver



(Except for 12V)

Features

- Constant Voltage + Constant Current mode output
- Protection Functions: OCP,SCP,OVP,OTP
- IP67 rating for indoor or outdoor installations
- Output adjustable via potentiometer
- Typical lifetime>50000 hours
- 5 years warranty

Applications

- LED bay lighting
- LED stage lighting
- LED flood lighting
- LED strip lighting
- DMX control system

Description

ELG-300 series is a 300W LED driver featuring with constant current and Constant voltage mode design. ELG-300 operates from 100~305VAC and offers CV mode or CC mode applications. Thanks to the high efficiency up to 94%, with the fanless design, the ambient temperature can be operated for -40℃~+85℃ case temperature under free air convection. The design of metal housing and IP67 ingress protection level allows this series to fit both indoor and outdoor applications. Moreover the innovative environment-adaptive capability allows this series to reliably light on the LEDs for all kinds of application environments in almost any spots that may install LED luminaires in the world ,as to provide the optimal design flexibility for LED lighting system.

Model Encoding

ELG - 300 - 24 □

- Function mode option
- Rated output voltage(12/24V)
- Rated wattage
- Series name

Type	IP Level	Function	Note
A	IP67	Io and Vo adjustable through built-in potentiometer	In Stock

300W Constant Voltage + Constant Current LED Driver

ELG-300

SPECIFICATION


MODEL			ELG-300-12A	ELG-300-24A
OUTPUT	DC VOLTAGE		12V	24V
	CONSTANT CURRENT REGION Note.2		10~ 12V	14.4~ 24V
	RATED CURRENT	200VAC ~ 305VAC	22A	12.5A
		100VAC ~ 180VAC	18.7A	10.63A
	RATED POWER	200VAC ~ 305VAC	264W	300W
		100VAC ~ 180VAC	224.4W	255W
	RIPPLE & NOISE (max.) Note.3		150mVp-p	240mVp-p
	VOLTAGE ADJ. RANGE		11.2 ~12.8V	22.4 ~25.6V
	CURRENT ADJ. RANGE		11 ~ 22A	6.25 ~ 12.5A
	VOLTAGE TOLERANCE Note.4		±3.0%	±2.0%
	LINE REGULATION		±0.5%	±0.5%
	LOAD REGULATION		±2.0%	±1.0%
	SETUP, RISE TIME Note.6		500ms, 100ms/230VAC, 500ms, 100ms/115VAC	
	HOLD UP TIME (Typ.)		10ms/ 230VAC 10ms/ 115VAC	
INPUT	VOLTAGE RANGE Note.5		100 ~ 305VAC 142 ~ 431VDC (Please refer to "STATIC CHARACTERISTIC" section)	
	FREQUENCY RANGE		47 ~ 63Hz	
	POWER FACTOR		PF≧0.95/115VAC, PF≧0.93/230VAC, PF≧0.90/277VAC@full load	
	TOTAL HARMONIC DISTORTION		THD< 10%(@load≧50%/115VC,230VAC; @load≧75%/277VAC)	
	EFFICIENCY (Typ.)		91%	94%
	AC CURRENT		3A / 115VAC 1.6A / 230VAC 1.3A/277VAC	
	INRUSH CURRENT(Typ.)		COLD START 45A(twidth=1200μs measured at 50% Ipeak) at 230VAC; Per NEMA 410	
	MAX. No. of PSUs on 16A CIRCUIT BREAKER		2 units (circuit breaker of type B) / 4 units (circuit breaker of type C) at 230VAC	
	LEAKAGE CURRENT		<0.75mA / 277VAC	
PROTECTION	OVER CURRENT		95 ~ 108%	
			Constant current limiting, recovers automatically after fault condition is removed	
	SHORT CIRCUIT		Constant current limiting, recovers automatically after fault condition is removed	
	OVER VOLTAGE		13.5 ~ 17V	27 ~ 34V
			Shut down output voltage, re-power on to recover	
	OVER TEMPERATURE		Shut down output voltage, re-power on to recover	
ENVIRONMENT	WORKING TEMP.		Tcase=-40 ~ +85℃ (Please refer to " OUTPUT LOAD vs TEMPERATURE" section)	
	MAX. CASE TEMP.		Tcase=+85℃	
	WORKING HUMIDITY		20 ~ 95% RH non-condensing	
	STORAGE TEMP., HUMIDITY		-40 ~ +80℃, 10 ~ 95% RH	
	TEMP. COEFFICIENT		±0.03%/℃ (0 ~ 60℃)	
	VIBRATION		10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes	
SAFETY & EMC	SAFETY STANDARDS		UL8750(type"HL")(Except for 12V), CSA C22.2 No. 250.13-12; ENEC EN61347-1, EN61347-2-13 independent, EN62384; EAC TP TC 004; GB19510.1 , GB19510.14; KC61347-1,KC61347-2-13; IS15885(Part2/Sec13),IP67 approved	
	WITHSTAND VOLTAGE		I/P-O/P:3.75KVAC I/P-FG:2.0KVAC O/P-FG:1.5KVAC	
	ISOLATION RESISTANCE		I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25℃/ 70% RH	
	EMC EMISSION		Compliance to EN55015,EN61000-3-2 Class C (@load≧50%) ; EN61000-3-3;KN15	
	EMC IMMUNITY		Compliance to EN61000-4-2,3,4,5,6,8,11; EN61547, light industry level (surge immunity Line-Earth 6KV, Line-Line 4KV),KN61547	
OTHERS	MTBF		609K hrs min. Telcordia SR-332 (Bellcore) ; 191Khrs min. MIL-HDBK-217F (25℃)	
	DIMENSION		246*77*39.5mm (L*W*H)	
	PACKING		1.45 Kg; 9pcs /13.5Kg / 0.76CUFT	

NOTE

1. All parameters NOT specially mentioned are measured at 230VAC input, rated current and 25℃ of ambient temperature.
2. Please refer to "DRIVING METHODS OF LED MODULE".
3. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.
4. Tolerance : includes set up tolerance, line regulation and load regulation.
5. De-rating may be needed under low input voltages. Please refer to "STATIC CHARACTERISTIC" sections for details.
6. Length of set up time is measured at first cold start. Turning ON/OFF the driver may lead to increase of the set up time.
7. The driver is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.
8. This series meets the typical life expectancy >50,000 hours of operation when Tcase, particularly (tc) point (or TMP, per DLC), is 70℃ or less.
9. Please refer to the warranty statement on MEAN WELL's website at http://www.meanwell.com
10. The ambient temperature derating of 3.5℃/1000m with fanless models and of 5℃/1000m with fan models for operating altitude higher than 2000m(6500ft).
11. To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED driver can only be used behind a switch without permanently connected to the mains.
12. For any application note and IP water proof function installation caution, please refer our user manual before using. https://www.meanwell.com/Upload/PDF/LED_EN.pdf


■ Block Diagram

PFC fosc : 45KHz
PWM fosc : 100KHz



■ DRIVING METHODS OF LED MODULE

※ This series is able to work in either Constant Current mode (a direct drive way) or Constant Voltage mode (usually through additional DC/DC driver) to drive the LEDs.





Typical output current normalized by rated current (%)

In the constant current region, the highest voltage at the output of the driver depends on the configuration of the end systems.

Should there be any compatibility issues, please contact MEAN WELL.


■ OUTPUT LOAD vs TEMPERATURE





◎ If ELG-300 operates in Constant Current mode with the rated current, the maximum workable Ta is 40℃.


■ STATIC CHARACTERISTIC



※De-rating is needed under low input voltage.


■ POWER FACTOR (PF) CHARACTERISTIC

※ Tcase at 75℃



■ TOTAL HARMONIC DISTORTION (THD)


※ ELG-300-24A Model, Tcase at 75℃




■ EFFICIENCY vs LOAD

ELGC-300 series possess superior working efficiency that up to 94% can be reached in field applications.

※ ELG-300-24A Model, Tcase at 75℃




■ LIFE TIME



■ MECHANICAL SPECIFICATION

CASE NO.: 266A Unit:mm



• tc : Max. Case Temperature

■ INSTALLATION MANUAL

Please refer to : http://www.meanwell.com/manual.html