



## NeoLinear™ Mini Sideview Warm White 2000-2200K

### Features & Benefits

- ✓ IP67 Waterproof Coating
- ✓ Homogeneous Light output
- ✓ CRI Rating >90
- ✓ 3 Year Guarantee
- ✓ Ultra Flexible
- ✓ Professional Product
- ✓ 120° Beam Angle
- ✓ Multiple Applications

### Quick Specs

IP67		>90	24V	3yr
IP Rating	Colour	CRI Rating	Voltage	Guarantee


### Full Specification

Product Code:	100.938
Colour Temperature:	2000 - 2200K
Guarantee Period:	3 Years
Wattage:	30W
Current:	250mA/M
Input Power:	DC24V
PCB Weight:	2oz
Weight:	220g
Size:	4 x 8 x 5000mm Roll
Reel Length:	5 Metres
Beam Angle:	120 degrees
LED Spacing:	n/a
Power consumption p/m:	6W
Lumens p/LED:	7lm

Lumens p/m:	200lm
Millicandelas:	2100
CRI (Greater than):	>90
Dimmable:	Yes
Cut Intervals:	25mm
LED Qty:	240 p/m
LED Type:	SM2216
IP Rating:	IP67
Continuous run in mtrs:	5 metres
Average LED life:	50,000
Base type:	50cm tails at both ends
CE & ROHS:	Yes
Peelable back:	n/a
Product type:	Neon Flex Mini







### Schematic Drawing

Units: mm



### Operating Precautions:



1. Please handle carefully during installation.
2. Ensure the NEOLINEAR™ Mini only bends within its predetermined bend direction.
3. A minimum of two people are required for the installation of NEOLINEAR™ Mini.
4. NEOLINEAR™ Mini must not be bent sharply.
5. NEOLINEAR™ Mini must not be twisted, dropped, bent at a 90° angle or hung down.



### Product Accessories (Not included)



### Photometric Data



#### Color Parameters:

Chromaticity Coordinate: x=0.5070 y=0.4053/u'=0.2961 v'=0.5326  
 CCT=2121K(Duv=-0.0031) Dominant WL:Ld =588.9nm Purity=73.9%  
 Ratio:R=33.1% G=64.9% B=2.0% Peak WL:Lp=633.0nm FWHM=114.7nm  
 Render Index:Ra=91.4 AvgR=90.1 TM30:Rf=88 Rg=100  
 R1 =95 R2 =98 R3 =93 R4 =93 R5 =96 R6 =92 R7 =86  
 R8 =78 R9 =60 R10=97 R11=96 R12=83 R13=97 R14=97 R15=89

#### Photo Parameters:

Flux = 199.2 lm Eff. : 32.64 lm/W Fe = 809.4 mW  
 Scotopic:207.66 S/P:1.0424

#### Electrical parameters:




V = 23.998 V I = 0.2543 A P = 6.103 W PF = 1.000  
 LEVEL:OUT WHITE:OUT

# LED Technologies

Creative LED & Effect Technology for the Trade Professional

# NEOLINEAR™

## INSPIRATIONS



### Technical Support

If you require any technical support or have an enquiry, please do not hesitate to contact one of our LED technical expert on the contact information provided.

**Telephone:** 01260 540014

**Opening times:** Mon-Thur: 8:30am - 5:30pm / Fri: 8:30am - 5:00pm

**[www.ledtechnologies.co.uk](http://www.ledtechnologies.co.uk)**

## NEOLINEAR™

The above data are typical values and may vary +/- 10%.

Colour temperatures may vary up to +/- 10%

Cutting points may not be reconnected. Once cut this terminates the length.

We supply in 5 meter rolls with 50 cm tails at each end.

Extrusions & Accessories are an optional extra.

**We reserve the right to change specifications without notice - E&OE.**

**Maximum Daisy chain - 5mtrs**

